## LEGENDFex<sup>TM</sup> Highly flexible PEX heating tube with oxygen barrier

Manufactured from a proprietary polymer formulation which dramatically increases flexibility and maintains high strength.

Available in 3/8", 1/2", 5/8", 3/4" and 1" tube sizes. LegendFlex<sup>™</sup> delivers greater performance and flexibility than standard PEX. We are so confident in its performance we back it with a 30 year warranty.

LegendFlex is extremely flexible and very difficult to kink. In the unlikely event one should occur, simply repair it with a heat gun. No need to cut and use a coupling or replace the tubing.

LegendFlex tubing is also compatible with cold expansion type fitting systems (compliant with standards ASTM F2080 & ASTM F1960). Its strength, durability and thermal memory enables proper seal with crimp or expansion style connections.

Size

Description

## **Residential, commercial and industrial** applications include:

- Radiant Heating and Cooling
- Snow & Ice Melt
- GeoThermal
- Turf Conditioning

| PROPERTY:                       | VALUE:                           |
|---------------------------------|----------------------------------|
| Density                         | 58.6 lb/ft <sup>3</sup>          |
| Thermal conductivity            | 0.22 Btu ft/h ft <sup>2</sup> °F |
| Coefficient of linear expansion | 1.2 in. per 100 ft. per 10 °F    |
| Modulus of elasticity           | 78,300 psi                       |
| Oxygen permeation               | < 0.1 grams/m³/day               |
| Bend radius                     | < 5x tubing outside diameter     |

Meets the requirements of ASTM F876 and F877



The externally-extruded EVOH oxygen barrier reduces oxygen molecule permeation into the water. Compliant with standard DIN4726(<0.1 grams/m<sup>3</sup>/day)

## **Heating Tube**



LegendFlex<sup>™</sup> heating tube – Highly flexible PEX with oxygen barrier. Provides excellent flexiblity and thermal memory for easy installati

|      |  | (lbs) |
|------|--|-------|
| 3/8" | PEX TUBING WITH OXYGEN BARRIER - 500 FEET  | 20    |
| 3/8" | PEX TUBING WITH OXYGEN BARRIER - 1000 FEET | 40    |
| 1/2" | PEX TUBING WITH OXYGEN BARRIER - 300 FEET  | 15    |
| 1/2" | PEX TUBING WITH OXYGEN BARRIER - 500 FEET  | 25    |
| 1/2" | PEX TUBING WITH OXYGEN BARRIER - 1000 FEET | 50    |
| 5/8" | PEX TUBING WITH OXYGEN BARRIER - 400 FEET  | 28    |
| 5/8" | PEX TUBING WITH OXYGEN BARRIER - 1000 FEET | 70    |
| 3/4" | PEX TUBING WITH OXYGEN BARRIER - 100 FEET  | 10    |
| 3/4" | PEX TUBING WITH OXYGEN BARRIER - 500 FEET  | 50    |
| 3/4" | PEX TUBING WITH OXYGEN BARRIER - 1000 FEET | 100   |
| 1"   | PEX TUBING WITH OXYGEN BARRIER - 100 FEET  | 16    |
| 1"   | PEX TUBING WITH OXYGEN BARRIER - 500 FEET  | 80    |
|      |  |       |

| lation.         |                              |                               |
|-----------------|------------------------------|-------------------------------|
| Weight<br>(lbs) | Capacity<br>(size –gal./ft.) | Item Number                   |
| 20<br>40        | <b>3/8"</b> — 0.0051         | 850-125<br>850-129            |
| 15<br>25<br>50  | <b>1/2"</b> — 0.0096         | 850-133<br>850-135<br>850-139 |
| 28<br>70        | <b>5/8"</b> — 0.0138         | 850-144<br>850-149            |
| 10<br>50<br>100 | <b>3/4"</b> — 0.0189         | 850-151<br>850-155<br>850-159 |
| 16<br>80        | <b>1"</b> — 0.0312           | 850-161<br>850-165            |

\*NOTE: 3/8" and 1" available November 1, 2011







866-752-2055 866-752-2054 Fax www.legendhydronics.com

LH-LFFS

Legend Hydronics<sup>®</sup> is a division of Legend Valve & Fitting, Inc.