Specification Submittal



AquaHeat PEX-A Large Diameter Heating Pipe AquaHeat

JOB		REPRESENTATIVE	Pexheat.com	
ENGINEER	Brian Whitehurst	ORDER#	DATE	
CONTRACTOR		SUBMITTED BY	DATE	
PAGE #		APPROVED BY	DATE	

Qty/Length	Part #	Pipe OD	SDR	Comments
			11	
			11	

Natural PEX-A Large Diameter Heating Pipe with O₂ Diffusion Barrier

The AquaHeat Pex-A pipes are produced from special HMW-HDPE resins. The crosslinking is performed (peroxide method) during the production process, resulting in irreversible cross-links between adjacent P.E. chains. The crosslinking process renders the pipe improved mechanical process such as; resistance to corrosion and pressure at high temperature, exceptional high abrasion and superb chemical resistance, and excellent longevity at high temperatures. Product is coated with oxygen diffusion barrier which prevents oxygen from entering the heating system through the pipe wall. Covered by a thirty year manufacturers warranty.

, ,				
Technical Data	Value	Unit	Test Standard	
Density	938	kg/m³	ASTM F-876	
Impact Strength (at 20°C) (at 100°C)	No Failure No Failure	KJ/m² KJ/m²	DIN 53453	
Elongation at break (at 20°C) (at100°C)	350-550 500-700	%	DIN 53455	
Tensile Strength (at 20°) (at 100°C)	20-26 9-13	N/mm² N/mm²	DIN 53455	
Presure Temperature Characteristics	203°F @ 87 PSI (95°C @ 6 bar) 68°F @ 217.5 PSI (20°C @ 15 bar)			
Pressure Tested	290 PSI (20bar)		İ	



Manufacturing Standards			
ASTM	F-876/F-877		
ASTM	E-84		
ASTM	F-1960/F2080		
CSA	B137.5/LM101713		
DIN	4726/9		
IAPMO	С		
ICBO	ES ER-5258		
NSF	61 / RFH / 14		

Description	OD mm	Nominal in	SDR	Weight lbs/ft	Wall Thickness in
94040 PEX-A Pipe with O ₂ Diffusion Barrier (*)	40	1-1/4"	11	.282	.146
94050 PEX-A Pipe with O ₂ Diffusion Barrier (*)	50	1-1/2"	11	.437	.181
94063 PEX-A Pipe with O ₂ Diffusion Barrier (*)	63	2"	11	.692	.228
94075 PEX-A Pipe with O ₂ Diffusion Barrier (*)	75	2-1/2"	11	.9679	.268
94090 PEX-A Pipe with O ₂ Diffusion Barrier (*)	90	3″	11	1.49	.323
94110 PEX-A Pipe with O ₂ Diffusion Barrier (*)	110	4"	11	2.09	.394

(*) Sold per foot, please specify length



888-470-2757

Available at: