

ELECTRIC BOILERS
7 KW TO 36 KW

both ultra



MAXIMUM EFFICIENCY. OPTIMAL PERFORMANCE.

bth ULTRA™ electrical boilers are compact and highly performant. Available in a wide array of performance levels and voltages, these highly versatile systems are very energy-efficient and can be used for residential, commercial and institutional applications. Lightweight and robust, the **bth ULTRA™** is easily installed and can supply all types of hot water heating systems.



Peak-performance
heating systems

bth ultra

ELECTRIC BOILERS
7 KW TO 36 KW

Reliability and performance in compact sizes.

bth ULTRA™ electric boilers are available in a wide variety of performance levels, from 7 kW to 36 kW, and with multiple voltage options. They can meet any—and all—of your hydronic heating needs.

Whether you need to heat a condominium, single-family home or commercial building, **bth ULTRA™** is an ultra-silent solution for new installations or replacement of an existing system. Its compact size is ideal for small spaces. In addition, the piping can be connected in multiple ways, making the on-wall boiler installation very easy.

The **bth ULTRA™** can be combined with an auxiliary heater for a dual-energy system. Thanks to its **T2 UltraSmart®** controller, the boiler provides optimal comfort with accurate temperature management.

Producing no combustion or GHG emissions, the **bth ULTRA™** is a highly energy-efficient and green alternative. Maintenance is simple and kept to a minimum.

THE BTH ULTRA™ BOILERS ARE IDEAL FOR HEATED FLOORS, RADIATORS AND HOT WATER BASEBOARDS.

OUR BOILERS CAN ALSO BE THE PERFECT SOLUTION TO COMPLEMENT YOUR EXISTING GEOTHERMAL, HEAT PUMP, BIOMASS OR SOLAR ENERGY HEATING SYSTEM.





The intelligent **T2 UltraSmart**® controller modulates the power level based on the system requirements and adjusts the water temperature based on outdoor temperature.

- Accurate and easily configurable **T2 UltraSmart**® controller with backlight display
- Preset configurations based on heating distribution system
- Outdoor sensor that modulates boiler water temperature
- The **T2 UltraSmart**® controller enables users to view the boiler's operation status at a glance

bth ULTRA™

7 KW TO 36 KW

- Heating stops when outside temperature gets warmer
- "Boost" mode that automatically increases the temperature when needed
- Works only when triggered by the thermostat
- Ability to purge the pump when system is not running
- Adjustable between 50 °F and 190 °F
- Safety control to limit excessively high temperatures
- Electrical supply and heat pump contact (contact only with commercial boilers)
- Breakers with 33 & 36 kW residential models
- 24 V electrical supply for thermostat and other accessories
- 30 PSI safety relief valve
- Drain/purge valve

bth ULTRA™ RESIDENTIAL COMMERCIAL



| | | | | |
|-----------------------------------|---------------|-------------------|-------------------|-------------------|
| MODEL | 12 to 24 kW | 27 to 29 kW | 33 to 36 kW | 7 to 36 kW |
| WEIGHT | 63 lb | 75 lb | 75 lb | 75 lb |
| VOLUME | 2 US gallons | 3 US gallons | 3 US gallons | 3 US gallons |
| MAXIMUM OPERATING PRESSURE | 30 PSI | 30 PSI | 30 PSI | 30 PSI |
| MECHANICAL CONNECTION | 1" NPT female | 1 1/4" NPT female | 1 1/4" NPT female | 1 1/4" NPT female |

RESIDENTIAL 240 VAC / 60 Hz / 1 phase¹

| Model | Power ² | | Amps ³ | 240 V Elements | Stages | Recommended electrical supply ⁴ | | |
|--------------|--------------------|---------|-------------------|-----------------------|--------|--|------------------------------|---------------|
| | kW | BTU/h | | | | Cu Wire | Al Wire | Breaker |
| BTH ULTRA 12 | 12 | 40 944 | 50.0 | 4 x 3 kW | 4 | 6 | 4 | 70 |
| BTH ULTRA 15 | 15 | 51 180 | 62.5 | 2 x 3 kW + 2 x 4.5 kW | 4 | 6 | 4 | 80 |
| BTH ULTRA 18 | 18 | 61 416 | 75.0 | 4 x 4.5 kW | 4 | 4 | 2 | 100 |
| BTH ULTRA 20 | 20 | 68 240 | 83.3 | 4 x 5 kW | 4 | 3 | 2 | 110 |
| BTH ULTRA 24 | 24 | 81 888 | 100.0 | 4 x 6 kW | 4 | 2 | 0 | 125 |
| BTH ULTRA 27 | 27 | 92 124 | 112.5 | 6 x 4.5 kW | 6 | 1 x 1 or 2 x 6 ⁴ | 1 x 00 or 2 x 4 ⁴ | 2 x 80 or 150 |
| BTH ULTRA 29 | 29 | 98 948 | 120.8 | 4 x 5 kW + 2 x 4.5 kW | 6 | 1 x 1 or 2 x 6 ⁴ | 1 x 00 or 2 x 4 ⁴ | 2 x 80 or 175 |
| BTH ULTRA 33 | 33 | 112 596 | 137.5 | 3 x 5 kW + 3 x 6 kW | 6 | 2 x 4 ⁴ | 2 x 2 ⁴ | 2 x 100 |
| BTH ULTRA 36 | 36 | 122 832 | 150.0 | 6 x 6 kW | 6 | 2 x 4 ⁴ | 2 x 2 ⁴ | 2 x 100 |

¹ Electric supply 120/240 V or 120/208 V 1 phase (L1-N-L2) with three 90 °C conductors and a ground or two conductors with a ground if the boiler does not require a 120 VAC pump or accessories.

² Multiply by .75 for 208 VAC supply. ³ Multiply by .867 for 208 VAC supply. ⁴ See Installation Manual.

COMMERCIAL 208 VAC / 60 Hz / 3 phases¹

| Model | Power ² | | Amps ³ | 240 V Elements | Stages | Recommended electrical supply ⁴ | | |
|--------------|--------------------|--------|-------------------|-----------------------|--------|--|---------|---------|
| | kW | BTU/h | | | | Cu Wire | Al Wire | Breaker |
| BTH ULTRA 7 | 7 | 22 860 | 18.8 | 3 x 3 kW | 1 | 10 | 10 | 30 |
| BTH ULTRA 10 | 10 | 34 461 | 28.2 | 3 x 4.5 kW | 1 | 8 | 6 | 40 |
| BTH ULTRA 11 | 11 | 38 214 | 31.4 | 3 x 5 kW | 1 | 8 | 6 | 40 |
| BTH ULTRA 13 | 13 | 46 062 | 37.6 | 6 x 3 kW | 2 | 8 | 6 | 50 |
| BTH ULTRA 17 | 17 | 58 004 | 47.1 | 3 x 3 kW + 3 x 4.5 kW | 2 | 6 | 6 | 60 |
| BTH ULTRA 20 | 20 | 68 922 | 56.5 | 6 x 4.5 kW | 2 | 6 | 4 | 80 |
| BTH ULTRA 22 | 22 | 76 770 | 62.7 | 6 x 5 kW | 2 | 6 | 4 | 80 |
| BTH ULTRA 25 | 25 | 84 276 | 69.0 | 3 x 5 kW + 3 x 6 kW | 2 | 4 | 3 | 90 |
| BTH ULTRA 27 | 27 | 92 124 | 75.3 | 6 x 6 kW | 2 | 4 | 2 | 100 |

¹ Electrical supply 208 V or 240 V 3 phases (L1-L2-L3) with three 90 °C conductors and a ground.

² Multiply by 1.34 for 240 VAC supply. ³ Multiply by 1.15 for 240 VAC supply.

COMMERCIAL 480 VAC / 60 Hz / 3 phases¹

| Model | Power | | Amps | 277 V Elements | Stages | Recommended electrical supply ⁴ | | |
|--------------|-------|---------|------|----------------|--------|--|---------|---------|
| | kW | BTU/h | | | | Cu Wire | Al Wire | Breaker |
| BTH ULTRA 15 | 15 | 51 180 | 18.0 | 3 x 5 kW | 1 | 10 | 10 | 30 |
| BTH ULTRA 18 | 18 | 61 416 | 21.6 | 3 x 6 kW | 1 | 10 | 10 | 30 |
| BTH ULTRA 30 | 30 | 102 360 | 36.1 | 6 x 5 kW | 2 | 8 | 6 | 50 |
| BTH ULTRA 36 | 36 | 122 832 | 43.3 | 6 x 6 kW | 2 | 6 | 4 | 60 |

¹ Electric supply 480 V 3 phases (L1-L2-L3) with three 90 °C conductors and a ground.

COMMERCIAL 600 VAC / 60 Hz / 3 phases¹

| Model | Power | | Amps | 347 V Elements | Stages | Recommended electrical supply ⁴ | | |
|--------------|-------|---------|------|-----------------------|--------|--|---------|---------|
| | kW | BTU/h | | | | Cu Wire | Al Wire | Breaker |
| BTH ULTRA 9 | 9 | 30 708 | 8.7 | 3 x 3 kW | 1 | 14 | 12 | 15 |
| BTH ULTRA 13 | 13 | 44 356 | 12.5 | 3 x 4.5 kW | 1 | 12 | 10 | 20 |
| BTH ULTRA 18 | 18 | 61 416 | 17.3 | 6 x 3 kW | 2 | 10 | 10 | 30 |
| BTH ULTRA 22 | 22 | 75 064 | 21.2 | 3 x 3 kW + 3 x 4.5 kW | 2 | 10 | 10 | 30 |
| BTH ULTRA 27 | 27 | 92 124 | 26.0 | 6 x 4.5 kW | 2 | 8 | 6 | 40 |
| BTH ULTRA 30 | 30 | 102 360 | 28.9 | 6 x 5 kW | 2 | 8 | 6 | 40 |
| BTH ULTRA 36 | 36 | 122 832 | 34.6 | 6 x 6 kW | 2 | 8 | 6 | 50 |

¹ Electric supply 600 V 3 phases (L1-L2-L3) with three 90 °C conductors and a ground.

⁴ The wire gauges and breaker capacity must be in conformity with the standards of the National Electrical Code (NEC), Canadian Electrical Code (CEC) and local codes (if applicable).

15-YEAR WARRANTY
ON THE RESERVOIR

2-YEAR WARRANTY
ON ELECTRICAL AND MECHANICAL PARTS



Thermo 2000 manufactures peak-performance heating systems for domestic hot water and hydronic heating systems. Since 1978, the company's innovations have provided sustainable solutions for residential, commercial and institutional applications.

THERMO 2000 Inc.
500 9th Avenue
Richmond, QC J0B 2H0

1 888 854-1111 Toll-free
819 826-5613 Telephone
819 826-6370 Fax

thermo2000.com