

HGT SERIES / Fixed bladder expansion tank

/ N I	


Representative:	Project:
Date Submitted:	Submitted by:
Date Approved:	Approved by:
Model Number:	Quantity:

DESCRIPTION

The expansion tank from the HGT Series are offered in sizes going from 2 to 13 gallons. These expansion tanks are build of two welded part to resist high pressures for a secure installation. The EPDM bladder separates the air from the water inside the tank saving space and energy. These devices are suitable for hot water, solar and cooling in addition to being compatible with glycol.

- Acceptance factor of 100%
- Water remains permanently separated from the air throughout the useful life of the installation
- ▶ The water does not escape the circuit. The steel tank never comes into contact with water
- Pre-charged at the factory to 12 PSI; tank need to be adjusted on site at the system operating pressure

Model#	Values	Conn. MNPT	Pre- charge	Max. temp.	Maximum operating	Dimension			W/a i a la k			
	Volume					Α		В		Weight		
	gal	L	101101	onargo ton	tompi	pressure	in	mm	in	mm	lb	kg
HGT-15	2.1	8	1/2"	12 PSI	240°F	115 PSI	7.9	200	13.7	348	5	2
HGT-30	4.8	18	1/2"	12 PSI	240°F	115 PSI	10.6	270	16.3	415	9	4
HGT-60M	6	23	1/2"	12 PSI	240°F	115 PSI	10.6	270	18.9	480	9.25	4.2
HGT-60	8	30	1/2"	12 PSI	240°F	115 PSI	13.8	350	17.9	455	14	6
HGT-90	13	50	1"	12 PSI	240°F	115 PSI	14.9	380	23.0	585	23	10



TYPICAL SPECIFICATIONS

Furnish and install, as shown on the plans, a _____ gallons/liters____ in/mm diameter × ____ air precharged steel expansion tank, with an EPDM fixed bladder that separate water from touching the steel shell of the tank. tire valve) to facilitate the on-site charging of the tank to meet system requirements. Each tank shall be a CALEFACTIO model #GT-_____ or approved equal.

Quebec (Canada)

T 450 951.0818

F 450 951.2165